



## Signature Colors® Tuscan Accents Base Coat



### Product Description

Tuscan Accents Base Coat is the first step of a two-step process. This special step forms an absorbent base coat under Signature Colors Tuscan Accents to create a two-color finish resembling antique Italian finishes in its unmistakable warmth and character.

### Features

- Unique Interior Faux Finish
- Specially Formulated For Use Under Tuscan Accents

### Recommended Uses

- Wallboard
- Plaster
- Wood
- Masonry
- Brick

### Colors and Base Information

	oz./gal.
Basecoat	128

Reference Lowe's store Database for available colors.

### Shipping and Packaging

**Freight Classification:** Paint or Paint Related Material. Protect from freezing.

**Packaging:** Gallon – 2 per carton

### Typical Properties (222389)

**Vehicle Type:** Vinyl Acetate Ethylene Resin

**Sheen:** 0 – 5 Units @ 85° angle

**Solids by Volume:** 26%

**Solids by Weight:** 43%

**Weight per Gallon:** 10.8 lbs./gal.

**VOC:** Less than 50 g/L

**Viscosity:** 98 – 108 Krebs Units

**Dry Time:** 77°F @ 50% Relative Humidity

**To the touch:** 1 hour(s)

**Recoat:** 24 hour(s)

**Washing:** Allow at least 7 days before washing. Use mild detergent and sponge.

**Full Cure:** 1 day(s)

**Surface Coverage:**

400 sq. ft./gal.

**At:** 4.0 mil Wet, 1.0 mil Dry

### Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

## Surface Preparation

Read the Lead Warning in Cautions section. **For New or Bare Surfaces:** New wallboard and plaster should be fully cured and clean. Remove all sanding dust. New walls must be primed with a latex wall primer. **For Previously Painted Surfaces:** All surfaces should be clean and dry and free of peeling and chipping paint. Patch any cracks; sand lightly and remove all sanding dust. Dull glossy surfaces with sandpaper or liquid gloss remover. Remove all sanding dust and wipe with damp cloth before applying.

## Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Mix thoroughly before and during use. Apply product with a 3/8" or 1/2" nap roller. Roll product in one heavy, full coverage coat, or two thin coats. Finish with long, even strokes in one direction. Allow to dry 24 hours before applying Signature Colors Tuscan Accents. Clean tools and hands with warm, soapy water.

## Cautions (222389)

**WARNING: CONTAINS CRYSTALLINE SILICA.** May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

**Warning:** This product contains chemicals known to the State of California to cause cancer.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long term exposure:** Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than 50 g/L VOC**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.