

**PDS #121**  
**PRODUCT INFORMATION**

1191 Wheeling Road, Wheeling, IL 60090  
 Phone: 847-541-9000 Fax: 847-541-7549



**24892 Valspar Ultra Premium Interior Flat Ceiling Paint**

**PRODUCT: 24892**

**DESCRIPTION:**

Valspar Ultra Premium Interior Flat Ceiling Paint

**FEATURES:**

An elegant flat finish to enhance the ceilings throughout your home with just one coat. This high performance ceiling finish goes on brilliant white for a fresh, crisp look or is tintable to over 100 colors so you're sure to find the right color to fit your style. Guaranteed to last a lifetime.

**WHERE TO USE:**

Properly prepared, durable interior textured or plain ceiling surfaces including previously painted and primed plaster, drywall and acoustical tile.

**SURFACE PREPARATION:**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces.

**Acoustical Tile:**

Vacuum or dust tiles to remove embedded dust. To maintain the sound absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Test vinyl-coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations.

**“Blown-on” Soft-Fibered Ceilings:**

Caution! All water-based paints will loosen or deteriorate a “blown-on” soft-fibered ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-based primer may help minimize the deterioration. Do not use a latex primer.

**TYPICAL PRODUCT PROPERTIES:**

VEHICLE TYPE: Acrylic Resin  
 SOLIDS: 52% WT. 33% VOL.  
 VOC: 100 g/l max  
 WT/GAL: 11.6 lbs.  
 VISCOSITY: 97-103 KU  
 FLASHPOINT: N/A  
 85° GLOSS: 0-2 Units

**COVERAGE:**

One gallon covers up to 400 sq. ft. (37.2m<sup>2</sup>), significantly less on acoustical tile.

**FILM THICKNESS:** 4.0 Mil Wet  
 1.2 Mil Dry

**DRYING TIME:**

Dries to the touch in 30-60 minutes. Paint only when surface and air temperatures are 50-90°F (10-32°C). Recoat in 2-4 hours.

**APPLICATION:**

Stir paint thoroughly. Apply with a premium quality roller, polyester brush or airless sprayer. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long even strokes in one direction.

**Washing Instructions:**

Wait at least 7 days before washing with a mild detergent and soft sponge.

**STORAGE AND DISPOSAL:**

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter.

Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**THINNING/CLEAN-UP:**

Thin only for spray application with up to 8 oz. of water per gallon of paint. Clean tools and hands with warm, soapy water.

**PACKAGING:**

Quarts	4 Pack
Gallons	4 Pack
5 Gallon Pail	Each

**Product Information Hotline:  
1-888-313-5569**

**TYPICAL ANALYSIS**

<b>CAS. NO.</b>	<b>INGREDIENTS</b>
7732-18-5	Water
14808-60-7	Crystalline Silica
13463-67-7	Titanium Dioxide
22708-90-3	Clay
Not Avail.	Vinyl Acetate Ethylene Copolymer
14464-46-1	Silica

**CAUTIONS:**

**CONTAINS CRYSTALLINE SILICA**

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

**FIRST AID:**

**EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.**

**IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long-term exposure:**

Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends on duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than  
100 g/L VOC (0.83 lb./Gal VOS)**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.