

SPEC #160
PRODUCT INFORMATION

valspar

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



40241 Series Valspar Ultra Premium Interior High Gloss Enamel

PRODUCT: 40241 Series

DESCRIPTION:

Valspar Ultra Premium Interior High Gloss Finish

FEATURES:

Use Valspar Ultra Premium 100% Acrylic Interior Paint for the interior protection and preservation of historic residences and newer homes too. The high gloss finish provides long lasting beauty and tough, enamel-like durability for all rooms and surfaces. Withstands repeated washings. Especially recommended for use in areas where repeated washing would be required: doors, trim, kitchens, bathrooms, children's rooms and hallways. Safe for children's rooms.

WHERE TO USE:

Properly prepared interior surfaces including previously painted and properly primed walls, plaster, wood, brick, wallboard, wallpaper, cement and metal. NOTE: Not for use in areas constantly exposed to water such as shower stalls, etc.

SURFACE PREPARATION:

General: Clean and dry surface thoroughly, removing dirt, dust, rust, grease and wax. Scrape off loose paint and wallpaper. Remove glue, shellac and sizing. Patch cracks and spot prime. Dull glossy surfaces with gloss remover or sandpaper. **Wallboard:** Smooth tape joints and wipe all powdery dust from surface. Prime with Valspar Interior Latex Drywall Primer. **Plaster:** Must be dry, fully cured and in good condition. Remove chalky residue and prime unpainted plaster with Valspar Interior Latex Drywall Primer. **Concrete/Masonry:** Must be dry, fully cured and in good condition. Remove any powdery dust and efflorescence. Prime with Valspar Interior Latex Drywall Primer. Fill the pores of concrete block with Latex Block Filler. Soft concrete or masonry surfaces should be primed with a masonry conditioner. **Ferrous Metal:** Remove all rust and oil from surface. Prime ferrous metal surfaces with rust inhibitive metal primer. **Galvanized Metal:** Remove all rust and oil from surface. Spot prime rusty areas with a rust inhibitive metal primer. **Wallpaper:** Painting over wallpaper is not recommended. If removal is not possible test pattern for bleeding. If bleeding occurs, remove paper or prime with Oil Stain Killer. **Wood:** Smooth new wood surfaces by sanding. Prime with Acrylic Enamel Undercoater.

TYPICAL PRODUCT PROPERTIES: 40241

VEHICLE TYPE: Acrylic Resin
SOLIDS: 46% WT. 34% VOL.
VOC: 250 g/l max
WT/GAL: 10.2 lbs.
VISCOSITY: 86-92 KU
FLASHPOINT: N/A
60° GLOSS: 75+ Units

COVERAGE:

400 Sq. Ft. - Gallon, depending on porosity.

FILM THICKNESS: 4.0 Mil Wet
1.5 Mil Dry

DRY TIMES:

This premium latex paint will dry to the touch in about an hour. Optimal room temperature between 50-90° F. If a second coat is desired, wait 2-4 hours before applying. Remember high humidity or cooler conditions will lengthen dry times.

APPLICATION:

1. Stir paint thoroughly. The following applicators can be used: **Brush:** Use a premium quality polyester brush. **Roller:** Use a premium quality polyester roller with 3/8 to 1/2 inch nap. **Airless spray:** Thinning is not usually necessary. Use 2000 psi with a 0.015 to 0.021 tip. **2.** Paint ceiling first. Brush 3" border around edges. Beginning at a corner work across the ceiling in 3-foot sections. For each section, spread the paint in a V Pattern, then fill in with even strokes. Finish with long, even strokes across the ceiling. **Tip:** Always roll from dry area into wet and work quickly to avoid lap marks. **3.** Next, paint one wall at a time. Brush a 3" border around the ceiling, floor, trim edges and corner. **4.** Roll the wall. Begin at a ceiling corner and work down the wall in 3-foot square sections. Follow the V pattern as outlined above. Finish by rolling from ceiling to floor. Continue this pattern across the wall. **Tip:** Work with a partner. One person uses a brush to paint the border, while the other follows with a roller to paint the wall. This ensures a "wet edge" between the brush and roller applied paint, preventing unsightly banding. **5.** Paint the trim. A 1"-2" brush is suitable for sashes, moldings and woodwork. You may wish to use the same paint color as the wall or contrast it with another color from our coordinating palette. **Cleaning your painted surface:** Dirt, stains and soils wash off easily from your painted surface with a mild, non-abrasive cleanser and a soft sponge. However, wait at least 7 days after painting to allow the paint to cure before you wash the surface.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

THINNING/CLEAN UP:

Clean up with warm soapy water. Do not thin.

PACKAGING:

4 Pack Quart	White, Base 1, 2 & 4
4 Pack Gallon	White, Base 1, 2 & 4
5 Gallons Each	White, Base 1

Product Information Hotline: 1-888-313-5569

TYPICAL ANALYSIS 40241

C.A.S. NO.	INGREDIENTS
7732-18-5	Water
Unknown	Acrylic Emulsion
13463-67-7	Titanium Dioxide
57-55-6	Propylene Glycol
25265-77-4	Ester-Alcohol

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. When sanding wear a dust mask. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.** **Delayed effect from long-term exposure:** Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to sanding dust.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:**

1-888-345-5732

This product contains less than 250 g/L VOC (2.1 lb./Gal VOS)

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.