



Ultra Premium Exterior Latex Satin Series



Product Description

Valspar® Ultra Premium Satin Finish exterior paint guarantees a lifetime of beautiful protection. The durable and versatile satin sheen won't peel, blister or fade, ensuring long lasting color. Gives a mildew resistant coating.

Features

- 100% Acrylic Latex
- Long Lasting Durability
- Thick, One Coat Coverage
- Superior Fade Resistance
- Gives Mildew Resistant Finish
- Soap & Water Clean-up

Recommended Uses

- Wood Siding & Trim
- Hardboard Siding; Fiber Cement Board
- Primed Metal; Weathered Steel
- Shakes; Asbestos Shingles
- Brick; Cement; Cinder Block
- Stucco; Concrete; Stone
- Aluminum & Vinyl Siding

Colors and Base Information

	oz./gal.
White	128
Base 1	126
Base 2	124
Base 4	116

Reference Lowe's store database for available colors.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart & Gallon – 4 per carton
5-gallon pail

Typical Properties (40245 White)

Vehicle Type: Acrylic Resin

Sheen: 15 – 21 Units @ 60° angle

Solids by Volume: 40%

Solids by Weight: 50%

Weight per Gallon: 10.5 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 95 – 100 Krieb Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 1 hour

Recoat: 4 hours

Surface Coverage:

400 sq. ft./gal. (27.9 - 37.2 m²) depending on surface porosity.

At: 4 mil Wet, 1.4 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all dirt, dust, chalk, rust, grease, wax and mildew. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin or eyes.

PDS 0100

Priming

Previously Painted Surfaces (including painted metal siding): Scrape off loose and peeling paint, sand, then prime. Thoroughly remove chalk by vigorous washing, then rinse. Dull glossy surfaces with gloss remover or sand paper. Countersink nails and apply an oil metal primer to exposed nail heads. Caulk cracks and joints, then prime.

Bare Wood: Coat knots and sappy areas with an exterior oil-based primer. Then prime entire area with an exterior oil-based or latex primer.

Hardboard Siding (unprimed, primed or previously painted): Remove wax from bleed-through areas with mineral spirits-soaked rags, turning often to avoid merely spreading wax around. Prime all hardboard with an exterior oil-based primer.

Vinyl Siding: Wash thoroughly and allow to dry. Then paint with a color lighter than original siding color. **WARNING** – Painting with darker colors will cause warping or deformation from heat absorption.

New Fiber Cement Board: Wash thoroughly and allow to dry. Prime with premium quality 100% acrylic exterior latex primer.

Masonry: Brush loose sand, dust and other material from the surface.

Metal: Use a galvanized metal primer on new galvanized surfaces or allow to age six months before painting, or clean with a mild muriatic acid solution. All iron and steel surfaces should be primed with a rust-inhibitive metal primer.

Application and Clean-up

Stir paint well and intermix containers of the same color. Apply product at temperatures ranging from 50 – 90°F (10 – 32°C). Use a premium quality roller or polyester brush to apply paint. Thin for spray application only with up to 8 oz. of water per gallon of paint. Start at the highest point of the house and work across. Always paint back into freshly painted areas and end up at a door, window or outer edge. Move windows after one hour to prevent sticking. Clean up with warm, soapy water.

Cautions (40245 White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after use.

Warning: This product contains a chemical known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

PDS 0100

valspar

1191 Wheeling Rd, Wheeling, IL 60090 888-313-5569
www.valspar.com

3/09