



Interior/Exterior Latex Tintable Color Primer



Product Description

Valspar Tintable Color Primer is the perfect beginning for deep, dark colored topcoats. This gray tinted premium quality primer promotes better hiding and truest color appearance – you’ll use fewer coats of paint. Many bold paint colors look truest when applied over one of 5 shades of gray. Color Primer also promotes better touch up and uniform color, eliminating streaks.

Features

- Improve Hide & Paint Color Appearance
- Low Odor
- Use Fewer Coats of Paint
- Dries in 30 Minutes

Recommended Uses

- Bare or previously painted drywall
- Masonry
- Concrete
- Cured plaster
- Wood
- Non-rusted galvanized metal, gutters, and downspouts

Colors and Base Information

	oz./gal.
Tintable Primer	116

Reference Lowe’s store Database for available colors.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart & Gallon – 4 per carton

Typical Properties (83059)

Vehicle Type: Acrylic Resin

Sheen: 4–12 Units @ 85° angle

Solids by Volume: 27%

Solids by Weight: 38%

Weight per Gallon: 9.9 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 95–110 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 30 minute(s)

Recoat: 2 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 1 day(s)

Surface Coverage:

400 sq. ft./gal.

At: 4.0 mil Wet, 1.1 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. **General:** Clean and dry surfaces thoroughly, removing all mildew, dirt, dust, rust and grease. **Previously Painted Surfaces:** Scrape loose and peeling paint, sand, then prime. Wire brush chalking areas and clean with TSP (or equivalent) and water. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails and apply a rust inhibitive metal primer on exposed nail heads. **Bare Wood:** Remove sap and clean knotty areas. Seal these areas by spot priming with Valspar Interior Oil Base Primer. **Wallboard, Tape Joints and Plaster:** Sand smooth, remove dust with damp cloth or sponge, then prime. **Masonry:** Brush loose sand, dust and other material from surface. **Metal:** May be used to prime weathered, non-rusted galvanized gutters and downspouts. New galvanized surfaces should be primed with a galvanized metal primer, or washed with a mild muriatic acid solution, or allowed to weather for 6 months before painting. All iron and steel surfaces should be primed with a rust inhibitive metal primer. **Clean Mildew from the Surface:** To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin or eyes.

Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Stir thoroughly before and during use. Apply with a premium quality polyester brush, “one coat” roller or airless sprayer. If applying by spray, back-roll or back-brush to work primer into the surface. Apply a liberal coat or primer uniformly, working well into the surface. Allow to dry at least 2 hours before applying a topcoat. **Tinting:** This product is to be tinted before use. The tinting color will not match topcoat color but will enhance topcoat color hide. Clean up with warm, soapy water.

Cautions (83059)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.